

Carpasol

Carpet cleaner for spray extraction machines

Features

Carpasol contains very effective, low-foaming surfactants which ensure a thorough cleaning of the carpet. Dirt is quickly dissolved and removed by the spray extraction method.

Ingredients (according to 648/2004/EC)

Anionic surfactants < 5%, nonionic surfactants < 5%, phosphates 5-15%, water-soluble solvents, maintenance substances, fragrances.
pH value (concentrate): approx. 9.5 pH value (ready-to-use solution): approx. 8.5

Application

Suitable for all colourfast and moisture-resistant textile floor coverings and textile covers.

Directions

Before application, vacuum carpet thoroughly.

Spray extraction:

Dilute 0.5-1 litre in 8 litres of cold water, depending on the degree of dirt.

Pour the cleaning solution into the fresh water tank and pre-spray stains. Using the adapter, apply in overlapping paths over the carpet. After application, raise the carpet nap and do not walk on the carpet until it has totally dried.

Textile pad method:

Dilute 100-150 ml in 1 litre of cold water, depending on the degree of dirt.

Pour the cleaning solution into a spray can. Spray onto a textile pad and place the pad under a rotary floor machine. Spray sparingly onto 1 m² of the carpet surface and shampoo the carpet in a circular motion. Turn or replace the textile pad.

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product.



**Carpet
cleaning**

Coverage per square metre

Spray extraction: 100 ml
Textile pad method: 5 ml

No consumer product according to 1999/44/EC Art. 1! For professional use only!

Packaging

10 litre container

Art. No. j 60 05 10
Protect from frost!

