

# Gommasol

## Rubber streaks remover

### Features

Gommasol is a solvent-based cleaner designed for the removal of rubber streaks and rubber residues caused by hand and forklifts on industrial floors. Thanks to its high cleaning effect, Gommasol can be used in very soiled industrial areas and warehouses. Gommasol has a low odour and applies easily.

### Ingredients (according to 648/2004/EC)

Nonionic surfactants 5-15%, water-soluble solvents, additives.

pH value (concentrate): approx. 6      pH value (ready-to-use solution): approx. 7

### Application

Suitable for use on all solvent-resistant floor coverings, such as industrial floors, concrete, epoxy resin, magnesite screed floors and clay floor tiles. Do not use on floors containing asphalt or bitumen or on plastic floors!

### Directions

Fill Gomasol (undiluted or diluted with water 1:1 to 1:2) into an appropriate spray application tool\* with foam nozzle, spray onto the floor and allow to act for approx. 10 minutes.

If the floor is normally soiled or if the product is applied locally, the dirty solution can be removed by mechanical wet cleaning with the automatic scrubber and a 1% solution of Dopomat-forte as part of the routine cleaning.

If the floor is heavily soiled or if the product is applied on a large surface, scrub the surface thoroughly with the rotary floor machine and a green pad after spraying. Then vacuum the dirty solution and rinse off thoroughly with clear water.

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product.

\* Appropriate application tools:

Art. No. VFK 28 00 50 Trigger spray bottle

Art. No. VVK 91 03 30 Foam nozzle for trigger spray bottle

Art. No. z 20 50 18 Spray bottle 1.5 L, Colour code: red, PP foam nozzle (EPDM seal)

Art. No. z 20 50 72 HQ pressurized sprayer, 5 L, RONDO, foam nozzle (EPDM seal)



**Cleaner for  
Automatic  
Scrubbers /  
Industrial  
cleaning**

### Coverage per square metre

Removal of rubber streaks: 50-100 ml

GHS 07, Warning (in concentrated form);

H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled. H315 Causes skin irritation.

H319 Causes serious eye irritation. P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/eye protection. P301+P330+P331 IF SWALLOWED: Rinse mouth.

Do NOT induce vomiting. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Contains Butoxyethanol (INCI).

**Not a consumer product according to 1999/44/EC Art. 1! For professional use only!**

### Packaging

5 L canister

Art. No. j 05 07 15

